



Take your Diesel to Where it's Needed

NS Diesel Tanks

This fantastic diesel tank allows you to take your diesel where it's needed when it's needed. Using a 12v diesel pump and available in a wide range of capacities from 100 litres up to 500 litres.

- 12V diesel pump
- High quality with an auto-shut off nozzle
- 4m of 3/4" delivery hose with swivel and crimped fittings included
- 4m of electrical cable with clamps
- Anti-Static leads exceeds the requirements of AS/NZS 1940:2004 and AS/NZS 2809.2:2008
- Tie down straps for safe transport
- Pad lockable filling cap

Available in 100, 200, 210, 400 and 500 litre tanks

NS AdBlue Tanks

Handling large diesel equipment or machinery and need a bigger AdBlue tank capacity? Our range of tanks will protect your AdBlue liquid from direct sunlight, extreme heat and cold temperatures. The range of NS AdBlue tanks are designed to provide maximum durability and extended performance. Perfect for mining, construction, industrial, and agriculture.

Available in 100 and 200 litre tanks

NS Diesel & AdBlue Tanks



Model	DD100	DD200	DD210	DD400	DD500	AD100	AD200
Liquid Storage	Diesel	Diesel	Diesel	Diesel	Diesel	AdBlue	AdBlue
Tank Size	100L	200L	210L	400L	500L	100L	200L
Pump Flow	40 LPM	40 LPM	40 LPM	40 LPM	40 LPM	40 LPM	40 LPM
Pump inlet/outlet size	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Pump Duty Cycle	30 min.	30 min.	30 min.	30 min.	30 min.	30 min.	30 min.
Pump Model	DP40012	DP40012	DP40012	DP40012	DP40012	DP40012	DP40012
Pump on/off switch	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Power Supply	12V	12V	12V	12V	12V	12V	12V
Delivery Hose Size	3/4" (19mm)	3/4" (19mm)	3/4" (19mm)	3/4" (19mm)	3/4" (19mm)	3/4" (19mm)	3/4" (19mm)
Delivery Hose Length	4m	4m	4m	4m	4m	4m	4m
Delivery Hose flame resistant abrasion cover	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Nozzle	Auto shut-off	Auto shut-off	Auto shut-off	Auto shut-off	Auto shut-off	Auto shut-off	Auto shut-off
Electrical cable length	4m	4m	4m	4m	4m	4m	4m
Electrical Clamps	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Anti-static leads that exceeds the requirements of AS/NZS1940:2004 and AS/NZS2809.2.2008	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Tie Down straps	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Pad lockable filling cap	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Fill opening size	120mm	120mm	120mm	120mm	120mm	120mm	120mm
Fill Cap Vent	Yes	Yes	Yes	Yes	Yes	Yes	Yes
External Dimensions	80x76x45cm	101x75x57cm	115x80x45cm	115x80x68cm	172x76x76cm	80x76x45cm	110x64x61cm
Dry Weight	23	27	35.8	53	57.6	23	27



For more information please call us on **1300 789 022** or email sales@claytonengineering.com.au